

M12 screw connection A-coded



SAIS / SAJB

Straight



SAISW / SAIBW

Angled



Ordering data

Male	
3-pole PG 7	
3-pole PG 9	
4-pole PG 7	
4-pole PG 9	
Female	
3-pole PG 7	
3-pole PG 9	
4-pole PG 7	
4-pole PG 9	
Note	

Type	Qty.	Order No.
SAIS-3/7	1	1021470000
SAIS-3/9	1	1021480000
SAIS-4/7	1	9457500000
SAIS-4/9	1	9883400000
Type	Qty.	Order No.
SAJB-3/7	1	1021490000
SAJB-3/9	1	1021510000
SAJB-4/7	1	9457240000
SAJB-4/9	1	9887200000
Other variants on request		

Type	Qty.	Order No.
SAISW-3/7	1	1021200000
SAISW-3/9	1	1021250000
SAISW-4/7	1	9457200000
SAISW-4/9	1	1007300000
Type	Qty.	Order No.
SAIBW-3/7	1	1021210000
SAIBW-3/9	1	1021230000
SAIBW-4/7	1	9457200000
SAIBW-4/9	1	1007240000
Other variants on request		

Technical data


Type of connection
Housing main material
Connection thread
Cable diameter
Wire cross-section, min. / max.
Rated current
Rated voltage
Temperature range of housing
Protection degree
Contact surface

Note

Screw connection
PA
M12
4...8 mm (PG7) / 8...9 mm (PG9)
3.14...3.75 mm²
4 A
250 V
-40...+85 °C
IP67
CuSnZn

Screw connection
PA
M12
4...8 mm (PG7) / 8...9 mm (PG9)
3.14...3.75 mm²
4 A
250 V
-40...+85 °C
IP67
CuSnZn

Dimensioned drawing



Dimensioned drawing

