

28500.4 KDS-SR 6/10 BK Screw frame



Cable entry with foamed-in seal, Mounting type: Screws, Length: 106 mm, Width: 70 mm, IP 66, Colour: Black

RAL: 9005

Business data

Product description	Cable Entry
Packaging unit	1
Quantity unit	PC
Weight per piece (not including packaging)	45.53
Weight per piece (including packaging)	66.53
Unit of weight	G
Customs number	39259020
Country of origin	DE

28500.4

KDS-SR 6/10 BK

Screw frame

Technical Data

Dimensions

Length	106 mm
Länge Wandausschnitt	68.5 mm
Width	70 mm
Breite Wandausschnitt	46 mm
Height	19.6 mm
Aufbauhöhe	19.6 mm
Durchmesser der Schraubenlöcher	5.5 mm

Materials

Material	Polyamide 6.6
Glass-fibre reinforced	✓
Flammability class UL 94	V-0
Working temperature, min.	-40 °C
Working temperature, max.	120 °C
Sealing material	Polyurethane-based
Type of seal	Sealing and moulded flexible foam
Halogen-free	✓
Silicone-free	✓

28500.4 KDS-SR 6/10 BK Screw frame

Technical Data

Further technical data

Mounting type	Screws
Protection	IP66
NEMA Type	4x
Anzahl der Schraubenlöcher	4
Befestigungsschrauben	M 5 (ISO 4762 / DIN 912)
Drehmoment der Befestigungsschrauben	3 Nm

28500.4 KDS-SR 6/10 BK Screw frame

Approvals

cUL approval

cUL approval	C22.2 No. 14-95
--------------	-----------------

cUL approval granted	✓
----------------------	---

UL approval

UL approval	UL 508
-------------	--------

UL approval granted	✓
---------------------	---

28502.4

KDS-SR 8/16 BK

Screw frame



Cable entry with foamed-in seal, Mounting type: Screws, Length: 126 mm, Width: 70 mm, IP 66, Colour: Black

RAL: 9005

Business data

Product description	Cable Entry
Packaging unit	1
Quantity unit	PC
Weight per piece (not including packaging)	58
Weight per piece (including packaging)	83
Unit of weight	G
Customs number	39259020
Country of origin	DE

28502.4

KDS-SR 8/16 BK

Screw frame

Technical Data

Dimensions

Length	126 mm
Länge Wandausschnitt	91 mm
Width	70 mm
Breite Wandausschnitt	46 mm
Height	19.6 mm
Aufbauhöhe	19.6 mm
Durchmesser der Schraubenlöcher	5.5 mm

Materials

Material	Polyamide 6.6
Glass-fibre reinforced	✓
Flammability class UL 94	V-0
Working temperature, min.	-40 °C
Working temperature, max.	120 °C
Sealing material	Polyurethane-based
Type of seal	Sealing and moulded flexible foam
Halogen-free	✓
Silicone-free	✓

28502.4

KDS-SR 8/16 BK

Screw frame

Technical Data

Further technical data

Mounting type	Screws
Protection	IP66
NEMA Type	4x
Anzahl der Schraubenlöcher	4
Befestigungsschrauben	M 5 (ISO 4762 / DIN 912)
Drehmoment der Befestigungsschrauben	3 Nm

28502.4 KDS-SR 8/16 BK Screw frame

Approvals

cUL approval

cUL approval	C22.2 No. 14-95
--------------	-----------------

cUL approval granted	✓
----------------------	---

UL approval

UL approval	UL 508
-------------	--------

UL approval granted	✓
---------------------	---