
# **Information on Components Used**



Connector	
Misumi	
DB-**S*	
<b>O</b> P.17	

EMI Countermeasure Hood	
Manufacturer	Misumi
Model Number	MDA-**H-***
More Information	OP.30









Female Connector	
Manufacturer	Hirose Electric Co., Ltd
Model Number	HIF3B*-***D-2.54*
Rated Current	1A
Rated Voltage	200 VAC
More Information	<b>○</b> P.48



**O**P.45



More Information



elding	Connector		
	Manufacturer	Sumitomo 3M	
	Model Number	101**-***0EL	
4	Rated Current	0.5A	
	Rated Voltage	150 VAC	
	Click Here for Details	<b>○</b> P.83	
,	Plastic Hood (40-co	re and 68-core are unavailable	
lan.	Manufacturer Sumitomo 3M		

More Information



More Information

**O**P.45

**O**P.85



MDR Connector (Pin)	
Model Number	FMCIE**MA**
Rated Current	1A
Rated Voltage	500V
Manufacturer	Misumi
Remarks	Not currently available for sale in Japan

**O**P.66



	MDR Shell	
Model Number	MPL**NK**ALS	
Specification	EMI Protection	
Materials	Nickel-plated Steel	
Manufacturer	Misumi	
Remarks	Not currently available for sale in Japan	

## PLC Compatible Cable Documents

Mitsubishi Electric

PLC Supported

Keyence PLC-supporting

Yokogawa Electric

PLC Supported

Fuji Electric PLC

Supported Cables

Terminal Block

Cables for PLC

Terminal Blocks

for PLC

Cables

Cables Omron PLC-supporting

Cables


### Multi-Core Cab



	Manufacturer	Misumi
.0	Model Number	SS30WS
VW-180	Standard Acquired	AWM20276
	Rated Temperature	80°C
	Flame Retardance	VW-1SC
	Bending Radius mm (Fixed Parts)	Finished Outer Diameter x 8
	Bending Radius mm (Movable Parts)	_
	More Information	OP.1339

~	Oubic		
	Other Than SB Cable	Manufacturer	Misumi
		Model Number	MAST-UL20276SB
		Standard Acquired	AWM20276
	976.92	Rated Temperature	0°C ~ 80°C
		Flame Retardance	_
		Bending Radius mm (Fixed Parts)	Finished Outer Diameter x 10
		Bending Radius mm (Movable Parts)	_
		More Information	<b>O</b> P.1333


A, B, C, D, E Cables	
_	
UL1007 Equivalent	
AWM1007	
0°C ~ 80°C	
_	
_	
_	
OP.1375 (Similar Specifications)	



# Crimp Terminal

Used for M3 / M3-5 screw terminal block

Y Terminal (0468) F0.08-3, F0.3-3, F1.25-3.51 Round Terminal (0464) 0.3-3



Single-Core Wire for Ground (Common for All Model Numbers)		
Model Number	UL1007-16-GN Equivalent	
Standard Acquired	UL1007	
Bending Radius	Finished Outer Diameter x 8	
More Information	OP.1375 (Similar Specifications)	



Crimp Terminal for Ground	
Model Number	RBA1.25-3.5RE Equivalent
Size	3.7mm
Outer Width	6.6mm
Rated Voltage	300V
More Information	<b>O</b> P.472