

# Leveling Mounts

Standard

Leveling Mounts – Standard

RoHS10

**NFJN**  
**NFJNS** Stainless Steel  
**NFJNF**

M	D	ℓ <sub>1</sub>	ℓ <sub>2</sub>	E	B	t
5	30	3.5	4	5.4	8	1.6
6		4	5		10	
8	38	5.5	6.5	11	13	
10		7	8		17	2.0
12	60	8	10	18	19	
16	75	10	13	20	24	
20		13	16		30	

Type	Material	Surface Treatment
NFJN	1018 Carbon Steel or Equivalent	Trivalent Chromate
NFJNF		
NFJNS	304 Stainless Steel	Electrolytic Polishing

## A Dimension Selectable

Part Number	M-A	L	Allowable Vertical Load (kN)	Mass (g)
<b>NFJN / NFJNS</b>				
5-30	40.5		1.5	15
5-60	70.5			19
6-40	51			21
6-80	91		2.1	28
8-50	68.1		3.9	50
8-100	118.1			65
10-75	94.6			88
10-100	119.6		4.3	100
12-50	78		4.9	142
12-75	103			166
12-100	128			184
12-125	153		5.9	200
12-150	178			219
16-75	107			287
16-100	132		8.8	317
16-130	162			356
16-150	182			383
16-180	212		422	
20-100	135		8.8	493
20-130	163			557
20-150	183			605
20-180	213			671

## A Dimension Configurable

Part Number	M	A	L
<b>NFJNF</b>			
10		80-200	A+19.6
12		80-250	A+28
16		80-300	A+32
20		110-300	A+35

⊙ Tips of screws are painted.

**Part Number Example**

Part Number - A

NFJN12-100 - 80

NFJNF10 - 80

**Part Number Example**

Part Number - (WC / WK / SC / WN)

NFJN16-75 - WC

⊙ For NFJN only.

⊙ No plating on alteration applied sections.

Alterations	Square Chamfering	Hex Chamfering	Wrench Flat	Hex Wrench Socket Machining																																																								
Code	WC	WK	SC	WN																																																								
Spec.	Ordering Code: WC ⊙ Applicable when M≥10 <table border="1"> <thead> <tr> <th>M</th> <th>WC</th> <th>ℓ</th> </tr> </thead> <tbody> <tr> <td>10</td> <td>6</td> <td>10</td> </tr> <tr> <td>12</td> <td>8</td> <td></td> </tr> <tr> <td>16</td> <td>10</td> <td>12</td> </tr> <tr> <td>20</td> <td>12</td> <td>13.5</td> </tr> </tbody> </table>	M	WC	ℓ	10	6	10	12	8		16	10	12	20	12	13.5	Ordering Code: WK ⊙ Applicable when M≥10 <table border="1"> <thead> <tr> <th>M</th> <th>WK</th> <th>ℓ</th> </tr> </thead> <tbody> <tr> <td>10</td> <td>6</td> <td rowspan="5">10</td> </tr> <tr> <td>12</td> <td>8</td> </tr> <tr> <td>16</td> <td>10</td> </tr> <tr> <td>20</td> <td>13</td> </tr> </tbody> </table>	M	WK	ℓ	10	6	10	12	8	16	10	20	13	Ordering Code: SC ⊙ Applicable when M≥10 <table border="1"> <thead> <tr> <th>M</th> <th>W</th> <th>ℓ<sub>1</sub></th> <th>SC</th> </tr> </thead> <tbody> <tr> <td>10</td> <td>8</td> <td>8</td> <td rowspan="5">20</td> </tr> <tr> <td>12</td> <td>10</td> <td></td> </tr> <tr> <td>16</td> <td>13</td> <td>10</td> </tr> <tr> <td>20</td> <td>17</td> <td></td> </tr> </tbody> </table>	M	W	ℓ <sub>1</sub>	SC	10	8	8	20	12	10		16	13	10	20	17		Ordering Code: WN ⊙ Applicable when M≥10 <table border="1"> <thead> <tr> <th>M</th> <th>WN</th> <th>ℓ</th> </tr> </thead> <tbody> <tr> <td>10</td> <td>4</td> <td>5</td> </tr> <tr> <td>12</td> <td>5</td> <td>6</td> </tr> <tr> <td>16</td> <td>8</td> <td>8</td> </tr> </tbody> </table>	M	WN	ℓ	10	4	5	12	5	6	16	8	8
M	WC	ℓ																																																										
10	6	10																																																										
12	8																																																											
16	10	12																																																										
20	12	13.5																																																										
M	WK	ℓ																																																										
10	6	10																																																										
12	8																																																											
16	10																																																											
20	13																																																											
M	W		ℓ <sub>1</sub>	SC																																																								
10	8	8	20																																																									
12	10																																																											
16	13	10																																																										
20	17																																																											
M	WN	ℓ																																																										
10	4	5																																																										
12	5	6																																																										
16	8	8																																																										

# Leveling Mounts

Non-Slip

Leveling Mounts – Non-Slip

Body	Type	(1) Main Body		(2) Rubber Part	
		Material	Surface Treatment	Material (Color)	Hardness
Steel	FJGN	1018 Carbon Steel or Equivalent	Trivalent Chromate	Elastomer (Black)	Shore A70
	FJGM			Neoprene Rubber (Black)	
				Non-migration Chloroprene Rubber (Gray)	
				Electrically Conductive Rubber (Black)	
Stainless Steel	FJGNS	304 Stainless Steel	Electrolytic Polishing	Elastomer (Black)	Shore A70
	FJGMS			Neoprene Rubber (Black)	
				Non-migration Chloroprene Rubber (Gray)	
				Electrically Conductive Rubber (Black)	

M	D	ℓ <sub>1</sub>	ℓ <sub>2</sub>	E	B	H
8	45	5.5	6.5	15	13	6
10		7	8		17	6
12	70	8	10	23	19	7
16		10	13		24	
20	80	13	16	25	30	8

⊙ Conductive Rubber Specific Volume Resistivity 10<sup>2</sup>-10<sup>4</sup> Ω-cm

⊙ Screw shaft turns independently of the base and tilts slightly

Part Number	FJGM / FJGMS	L	Vertical Allowable Load (kN)	Mass (g)	Available Types										
					FJGN	FJGM				FJGNS	FJGMS				
Type	M-A	Rubber Material			FJGN	R	C	D	S	FJGNS	R	C	D		
FJGN FJGM FJGNS Stainless Steel	8-50	R Rubber	70.5	3.9	•	•	•	•	—	•	•	•	•		
	8-100		120.5		•	•	•	•	—	•	•	•	•		
	10-75		97	4.3	•	•	•	•	—	•	•	•	•		
	10-100		122		•	•	•	•	—	•	•	•	•		
	12-75		106	C Non-Migration Chloroprene Rubber	4.9	•	•	•	•	—	•	•	•	•	
	12-100*		106			•	•	•	•	—	•	•	•	•	
	12-100*		131			•	•	•	•	•	•	•	•	•	•
	12-125*		156			•	•	•	•	•	•	•	•	•	•
	12-150		181	D Conductive Rubber	5.9	•	•	•	•	—	•	•	•	•	
	16-75		110			•	•	•	•	—	•	•	•	•	
16-100*	135	•	•			•	•	•	•	•	•	•	•		
16-130*	165	•	•			•	•	•	•	•	•	•	•		
16-150	185	S PVC	6.8	•	•	•	•	—	•	•	•	•			
16-180*	215			•	•	•	•	•	•	•	•	•			
20-100*	138			•	•	•	•	•	•	•	•	•	•		
20-130*	168			•	•	•	•	•	•	•	•	•	•		
20-150	188		6.8	•	•	•	•	—	•	•	•	•			
20-180*	218	•		•	•	•	•	•	•	•	•	•			

⊙ No selectable rubber material for FJGN and FJGNS. (Elastomer is used) \*PVC rubber applicable sizes

**Part Number Example**

Part Number - Rubber Material

FJGM16-75 - R