

Pipe Supports

Vertical Pipe Bands / Paddle-Shaped Legs

Pipes / Fittings / Hoses / Valves

Pipe Supports – Vertical Pipe Bands

Type	Material		Surface Treatment
	Standard	With Protection Material	
KBND	Low Carbon Steel	Flexible PVC (White)	Trivalent Chromate
KBNS	304 Stainless Steel	—	—

Standard

Non-Slip Seal
Hex Screw M6 x 20

With Protection Material Type

Hex Screw M6x20

* t of KBND means thickness of sheet metal. Thickness of protection material is (1.5).

Type	No.	Applicable Outer Dia. D	(L)	Material			W	C	P
				KBND	KBNS	KBND			
Standard Type	10A	17.3	73	1.8	2	—	25	45	20
	15A	21.7	77						
	20A	27.2	84						
	25A	34	88						
With Protection Material	32A	42.7	98	0.6	—	—	25	45	20
	40A	48.6	104						
	50A	60.5	116						

ⓘ Be sure to use KBND in ambient temperature up to 60°C for the properties of flexible PVC.

Pipe Supports – Paddle Shaped Legs

Type	Material	Surface Treatment
HGA	1018 Carbon Steel or Equivalent	Trivalent Chromate
HGAS	304 Stainless Steel	—

2-Slotted Hole
M10x22
Ø10

Type	No.	L
HGA HGAS	1	50
	2	75
	3	100

Pipe Supports – T-Shaped Legs

Type	Material	Surface Treatment
TGA	Low Carbon Steel	Trivalent Chromate
TGAS	304 Stainless Steel	—

2-Ø4.5
Slotted Hole

Type	No.	L	(L)
TGA TGAS	1S	50	26
	1	60	36
	2	80	56
	3	100	76

Part Number Example

Part Number: **KBND25A**
TGA2

Application Example

Suitable for holding pipes, such as a steel pipe nozzle.

Enlarged View of A

Piping Supports

Saddle Bands / Piping U-Bolt Sets

Pipes / Fittings / Hoses / Valves

Piping Supports – Saddle Bands

Type	Material		Surface Treatment
	Double-Sided	Single-Sided	
RSDLN	Low Carbon Steel	Flexible PVC (White)	Trivalent Chromate
RSDLNS	304 Stainless Steel	—	—

Double-Sided Type

Single-Sided Type

Double-Sided Type

Type	No.	Applicable Outer Dia. D	(L)		(P)		W
			RSDLN	RSDLNS	RSDLN	RSDLNS	
RSDLN RSDLNS	15A	21.7	60	60	47	47	19
	20A	27.2	65	65	52	52	
	25A	34.0	73	72	60	59	
	32A	42.7	81	86	68	73	21
	40A	48.6	86	88	73	75	
	50A	60.5	100	102	87	89	

Single-Sided Type

Type	No.	Applicable Outer Dia. D	(L)		t		W	
			KSDLN	KSDLS	KSDLN	KSDLS	KSDLN	KSDLS
KSDLN KSDLS	15A	21.7	45	49	1.6	1.2	25	20
	20A	27.2	50	54.5				
	25A	34	57	67				
	32A	42.7	71	75		2	25	25
	40A	48.6	77	82				
	50A	60.5	89	99				

Piping Supports – Piping U-Bolts

Type	Material	Surface Treatment	Accessories
UB	(Low Particle Generation Type)	Reference Mass (g/m)	Nut 2 pcs. (SWRCH Carbon Steel Trivalent Chromate)
UBSU	302HQ Stainless Steel (304 Stainless Steel)	—	Nut 2 pcs. (304 Stainless Steel)

UB
UBSU
Stainless Steel

Main Body
Included Nut

Type	No.	Applicable Pipe		M (Coarse)	(H)	L
		Applicable Diameter of Pipes	*Pipe Outer Dia. (mm)			
UB UBSU	3	10A	17.3	M4	34	21.3
	4	15A	21.7	M4	37	25.7
	4-M5			M5		26.7
	6	20A	27.2	M4	39	31.2
	6-M5			M5		32.2
	8	25A	34.0	M4	43	38
	8-M5			M5		39
	10	32A	42.7	M5	47	47.7
	10-M6			M6		48.7
	12	40A	48.6	M5	50	53.6
	16	50A	60.5	M5	57	65.5

ⓘ Outer diameter (mm) of pipes is for reference only.

Nut Size

M (Coarse)	B	C	T
M4	7	8.1	3.2
M5	8	9.2	4
M6	10	11.5	5

Part Number Example

Part Number: **RSDLN15A**
UB4
UBSU10-M6